2002 Harriston clodhopper 200

Date	Maintenance	Person responsible
Jul-19	Replaced all stars (purchased at Banga's)	
	Checked all bearings on star drives, replaced 4	
	Replaced upper and lower belted chain (purchased at Prairieside)	
	Replaced drive chain on both clod rollers and belted chain drives	
	Replaced all and Added superslide underneath the stars	
	Replaced both 30" product discharge belts	
	Fixed seals at 4 gearboxes	
	Changed oil on all gearboxes (80w90)	
	Converted to 480v, interlock installed	Rivers Electric
Aug-19	Changed 1 nose roller on bottom belted chain	
	Replaced drive sprockets on bottom belted chain	
Sep-19	Lacing 30" discharge temporarily fixed	
Oct-19	Lacing replaced on 30" discharge belt	
19-Nov	Hitch fixed	
Aug-20	Motor on discharge belt replaced (Southern Rewind)	
Sep-20	Motor on top diggerchain is loose, needs to be welded	
	Rerouted chain for intake belts	
	Installed superslide on discharge belts, installed holders for prybars	
Jan-21	Buzzer installed for starting up on Tab's request	Rivers electric
	Both emergency stops installed and wired into same system	
Feb-21	All rollers replaced on intake belts, was bushings, now bearings	
	2" inside diameter exhaust pipe (48049) at napa, bearings/hubs@Banga	
	Cleaned up all shafts in intake belts to make bearings slide on. Some shafts	
	had some wear where bushings sat.	
	Welded flatbars on both outsides top and bottom by	
	rollers to prevent little potatoes to get in belts, belts 28,5" wide	
	Shortened chain feeder belts 1 link. Alligned belts	
	Superslide under star table repaired.	
	30" discharge belt modified, return rollers were too high, lacing would rub	
	on frame 1*2 tubing. Rollers replaced with superslide. Rollers all good	
	Lacing replaced, 30" potato discharge belt cannot be shortened anymore.	
	Repaired wiring on bottom clod roller motor, was ripped off/temp fix	
	Adjusted scrapers on clodrollers	
	30" dirt belt under stars replaced. 15' 6" return roller removed.	
	30" potato belt replaced under 1st clodroller 15' 8" return rollers removed	
Jul-21	Clod fences replaced and rerubbered	
0 04	Put bolt/washer in shaft of clod roller to prevent motor from moving away	l .
	Motor on potato belt fried (motor was 1 year old) Southern Rewind warranty repla	acea I
Oct-21	Washed with t&t soap	
		I

MakeHarristonModelClodhopper 200Year2002Year of purchase2018

Daily maintenance when in use

Maintenance	Comment	Person resposible
Grease bearings as required	Boss, big blue MP2	Michiel
Oil chains as required	Use canola oil	Matthijs
Visual inspection	Check for leaks, broken,	
	loose or damaged parts,	
	maintenance or calibration needed	
Dry cleaning	Get rid of mud, soil, build-up etc	